


Small footprint, big results

Choose from canopy-mounted UV systems or slimline in-duct units



*Plasma Clean is continuously improving its products and services and reserves the right to alter designs without prior notice

The Techniclean Canopy Mount system breaks down kitchen smells and grease using photolysis and ozonolysis. It combines high-intensity UVC light with ozone technology to destroy grease and cooking odours.

The slimline, small-footprint design means you can get big results no matter how small the kitchen.

Benefits

- Slimline with a small footprint
- Plug-and-play setup
- Dramatically cuts ductwork cleaning
- Cost-effective with limited maintenance
- Lamp-life indicator for safety

Related products



Techniclean Mini

Simple to retrofit, the Techniclean Mini reduces grease in ventilation ductwork [Find out more](#)



Techniclean In-Duct Unit

Keep your ductwork virtually grease-free whilst reducing the risk of fire [Find out more](#)

plasma-clean.com • ask@plasma-clean.com | +44 (0)161 870 2325
Earl Business Centre, Dowry Street, Oldham, OL8 2PF

[f @PlasmaClean](#) [in /Plasma-Clean-LTD](#)



Introduction to Kitchen Ventilation from Plasma Clean

Grease, odour and smoke emissions produced by commercial kitchens are an increasing concern both for existing establishments and for new build projects. Therefore, it is essential to implement a suitable grease and odour control strategy - as a matter of urgency - to ensure that the kitchen emissions comply with DW/172 and DEFRA guidance. This is not just about protecting the environment from nuisance emissions, but also reducing grease build up in the ductwork, which could present a fire risk if left untreated.

Plasma Clean's Kitchen Ventilation range consists of a range of modular solutions for grease, smoke and odour control which can be used alone or can be combined to provide a site-specific solution. For example, a pizza restaurant will not require the same level of grease, odour and smoke control equipment as a char-grill steak house.

Starting at the canopy, our **Coil Filters** are designed to capture 95% of grease particles; between 55-70% more than traditional baffle-type filters. Our **Xtract** range releases natural ozone - a superb disinfectant and odour neutraliser - directly into kitchen ventilation systems. Our **Techniclean** range includes the canopy mounted **Techniclean CM**, combining high intensity UVC light with ozone technology to break down odour and grease in the air, as well as the **Techniclean Mini, 5000** and **7500** models; perfect for new projects or retrofitting into existing ductwork. High levels of grease and smoke particulate are treated by the **Electrostatix** and combining Electrostatic Precipitation with UVC, are our **ESP UV** units, provide highly efficient removal of grease, smoke and odour from a compact unit.

For a final polish - removing residual ozone - **Activated Carbon** filters are the ideal choice for low level extraction. Our Carbon Housing allows Activated Carbon filters to sit in 3, 6 or 9 easily mountable Sitesafe Discarb units.

When it comes to Control Panels, our **Air Flow Interlock** range is used to synchronise the operation of all of our Kitchen Ventilation products with detected air flow. The equipment is automatically turned off when the system is shut down, preventing accidental exposure to UVC light and ozone, whilst ensuring energy efficiency for the system. Options are available for Lamp Life Indicators, Lamp Fault and BMS interface.

Filtration with Techniclean from Plasma Clean

Oxidation of odour and grease by a combination of photolysis and ozonolysis is a recognised means of pollution abatement (DW/172: Specification for Kitchen Ventilation Systems and DEFRA, 2005:Guidance on the Control of Odour and Noise from Commercial Kitchen Exhaust Systems). The UVC light initially activates the grease and odour molecules which are then attacked by ozone in the kitchen extraction canopy or ductwork. This treats the air and controls grease deposits in the entire extraction system, reducing duct cleaning.

Installation

The system has been designed to sit in the canopy plenum to treat grease and odours. The system has a low back pressure and is to be interlocked with airflow to ensure that the system operates automatically when the extraction system is activated. Full installation and operating instructions are provided.

Accessories

Installation kit

Maintenance

Over time, and dependent on the usage frequency, a fine layer of ash is deposited on the UVC lamps. These require occasional cleaning by simply wiping with a damp cloth which has been soaked in detergent, and dried using an organic solvent. Maintenance and lamp replacement can be carried out under a Plasma Clean maintenance contract.

Warranty

1 year Manufacturer's Warranty (subject to terms and conditions)
Extended 3 year Warranty (care plan available)

Terms

In accordance with our standard terms of business.

Technical Specifications & Data

Dimensions (HWD)	400 x 600 x 300mm
No. of UVC lamps per rack	Up to 8 Air Flow and Service LED indicators
Supply	230Vac/ 1 phase / 50-60Hz
Power per tube	80 - 160W
Min / Max working temperature	4 / 60°C
Max relative humidity	75%
Noise	50dB
Pressure	<100Pa (with light guards)
Safety	Control Panel
Finish	Grade 304 stainless steel
Approvals	Plasma Clean air cleaners comply with current CE requirements and EMC standards. Certificates are available on request.

