


# Remove grease and oil particulate before they enter the kitchen canopy



Plasma Clean Air baffle filters provide optimum grease removal and flame protection in the kitchen canopy. The filters are tested to UL1046 - 'Grease Filters for Exhaust Ducts'. The rounded baffle design maximizes grease impingement and facilitates cleaning. The pressure drop at 100% rated air flow is 80Pa.

## **Benefits**

- Low static pressure ensures quiet operation
- High grease removal efficiency
- · Safe, dependable flame barrier protection
- · Self-balancing airflow throughout the entire length of one hood
- Easy installation/removal
- Comply with the DW/172 standard

#### **Related products**



**Grease Bloc Filter** 



**Electrostatic Grease Control** 

**plasma-cleanair.com** • ask@plasma-cleanair.com | 0800 652 3325 Earl Business Centre, Dowry Street, Oldham, OL8 2PF











## **Filter Specifications**

Model	Actual Size - H x W x D (mm)	Filter Weight (kg)	Rated Air Flow (m3/hr)
FRB1016	254 x 406 x 44	1.2	340
FRB1020	254 x 508 x 44	1.5	510
FRB1216	305 x 406 x 44	1.4	425
FRB1220	305 x 508 x 44	1.7	595
FRB1616	406 x 406 x 44	1.8	595
FRB1620	406 x 508 x 44	2.1	765
FRB1625	406 x 635 x 44	2.6	1020
FRB2016	508 x 406 x 44	2.1	765
FRB2020	508 x 508 x 44	2.5	1020
FRB2025	508 x 635 x 44	3.1	850
FRB2516	635 x 406 x 44	2.6	935
FRB2520	635 x 508 x 44	3.1	1275

#### **Installation**

Diirect replacement for standard baffle filters.

#### Maintenance

Depending on the level of cooking, the system can be washed daily or as part of a weekly cleaning routine.