



Self-Cleaning Filter Enhancement System

PRODUCT DESCRIPTION

The PF-i from GPS Air is a self-cleaning filter enhancement system. The Opti-Lok™ technology improves an air filters ability to capture sub-micron particles, making it more efficient. The unit is designed for mounting inside ducts and air handling units upstream of system filtration.

STANDARD FEATURES

- Opti-Lok™ technology
- Multi-voltage input
- Self-cleaning cycle
- Magnets for ease of installation
- Integral Building Automation System (BAS) alarm contacts



SPECIFICATIONS

Input Voltage	24-240 VAC	Unit Dimensions	7.3" L x 2.0" W x 4.3" H
Frequency	50/60Hz	Weight	1.42 lb
Power Consumption	11W (operating), 14W (cleaning cycle)	Alarm Contact Ratings	250 VAC / 1A, N.O. "dry" contact
Airflow Range	0 - 3,800 CFM	Electrical Listings	ETL (us, c)
Temperature / Humidity Range	-20°F to 140°F / 0 - 100% RH	Compliance & Certifications	UL 867. UL 2998, CARB, FCC part 18
Compatible Filter Types	Electrostatic Filters using Synthetic Media		



GPS Air Approved Partner
ask@plasma-cleanair.com
0800 652 3325
plasma-cleanair.com

